In the claims:

Amend the following claims:

1. A method of transmitting a position of a traffic information, in particular about a traffic obstruction on a traffic way in digital coding messages, comprising the steps of using for coding and decoding of messages transmitter- and receiver- side location data banks; coding a rough position of a traffic information by referencing to the traffic way and at least one location contained in the location data bank and located on the traffic way; and additionally to the location, transmitting a section part between the position and the location.

2. (currently amended) A method as defined in claim 1; and further comprising referring the section part to a section between thea coded location and a location on the traffic way which is spaced from the coded location by a measure.

3. (currently amended) A method as defined in claim 1; and further comprising referring the section part to a section between the a coded

ag Coxt. location and a location provided on the same traffic way immediately adjoining the coded location in the data bank.

- 4. (original) A method as defined in claim 1; and further comprising performing during a coding in accordance with ALERT-C protocol, performing the coding of the section part in Label 15.
- 5. (original) A method as defined in claim 1; and further comprising during a coding in accordance with ALERT-C protocol, performing the coding of the section part in Label 12.
- 6. (original) A method as defined in claim 1; and further comprising transmitting by means of the section portion a position of a beginning of a traffic obstruction; and calculating an end of the traffic obstruction from a length transmitted via Label 2.
- 7. (original) A method as defined in claim 1; and further comprising transmitting by means of the section part a position of a beginning of a traffic obstruction; and calculating an end of the traffic obstruction from a transmitted event code.

D9.

ag conta. 8. (original) A method as defined in claim 1; and further comprising when distance data in a location data bank of a receiver are not available, obtaining the distance data from a digital map associated with the receiver.